

PAC BT

LOW TEMPERATURE HEAT PUMP

Airwell
Just feel well



COP up to 4.85

EER up to 4.55



+ PRODUCTS

- Cooling and heating mode.
- Monobloc system.
- Available in 3PH (sizes 14 to 16).
- High flexibility due to DC Inverter compressor.

FEATURES



DC INVERTER



R410A FLUID



HEATING MODE
OPERATIONAL DOWN
TO -20°C OUTDOORS



DOMESTIC
HOT WATER



FLOOR HEATING



HIGH-TEMPERATURE
RADIATOR



ULTRA QUIET



WATER
PROGRAMMES



PAC BT 5-7 kW



PAC BT 9-10-12-14-16 kW

- Digital display on indoor unit: mode selection (heating, cooling and Domestic Hot Water), weekly timer and holidays, diagnosis aid (display parameters, troubleshooting).
- Provides optimal comfort all year long: Only one system for heating and cooling.
- Ideal solution for radiant panel in heating and cooling mode, low temperature heater, or fan-coil units.
- “Plug & Play” solution to replace old monobloc heat pumps.
- 4.58 to 16.30 kW in heating mode / 4.55 to 15.1 kW in cooling mode over 6 models
- Operating in heating mode up to -20°C outdoor temperature (water outlet temperature up to 60°C).
- Operating in cooling mode up to 46°C.
- Compact solution: small footprint
- Safety features included (safety valve, expansion tank).
- High performances: COP up to 4.85 and EER up to 4.55.
- Energy efficiency coefficient up to 178,3% (η_s).
- Auxiliary heat resistance included (depends on model - not included on sizes 5, 7 and 9).